

**SPECIFICATIONS**

A clean, contemporary sawn stone paired with an exotic, natural sparkling gray color.

**THIN VENEER**

<b>LENGTH</b>	4" - 30" Random
<b>HEIGHT*</b>	Sawn 2 1/4", 5", & 7 3/4"
<b>THICKNESS</b>	3/4" - 1 1/2"
<b>YIELD</b>	10-15 lbs/ft <sup>2</sup>

\*Typical height ratio: 20% = 2 1/4", 50% = 5", 30% = 7 3/4". Additional heights available upon request.

**ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY**

<b>WATER ABSORPTION</b>	.14%
<b>BULK SPECIFIC GRAVITY</b>	2.78

**ASTM C-170 – COMPRESSIVE STRENGTH**

<b>PARALLEL TO RIFT DRY</b>	22,230 psi
<b>PARALLEL TO RIFT, WET</b>	14,610 psi
<b>PERPENDICULAR TO RIFT, DRY</b>	23,510 psi
<b>PERPENDICULAR TO RIFT, WET</b>	14,040 psi

**ASTM C-99 – MODULUS OF RUPTURE**

<b>PARALLEL TO RIFT DRY</b>	2,040 psi
<b>PARALLEL TO RIFT, WET</b>	1,700 psi
<b>PERPENDICULAR TO RIFT, DRY</b>	4,070 psi
<b>PERPENDICULAR TO RIFT, WET</b>	1,700 psi

**ASTM C-880 – FLEXURAL STRENGTH**

<b>PARALLEL TO RIFT DRY</b>	1,640 psi
<b>PARALLEL TO RIFT, WET</b>	1,260 psi
<b>PERPENDICULAR TO RIFT, DRY</b>	2,840 psi
<b>PERPENDICULAR TO RIFT, WET</b>	2,440 psi



(573) 302-8855

