

SPECIFICATIONS

A clean, contemporary sawn natural stone in a traditional gray granite color.

	THIN VENEER
LENGTH	4" - 30" Random
HEIGHT*	Sawn 2 1/4", 5", & 7 3/4"
THICKNESS	3/4" - 1 1/2"
YIELD	10-15 lbs/ft ²

*Typical height ratio: 20% = 2 W, 50% = 5", 30% = 7 W. Additional heights available upon request.

ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.10%
BULK SPECIFIC GRAVITY	2.906

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	21,493 psi
PARALLEL TO RIFT, WET	21,626 psi
PERPENDICULAR TO RIFT, DRY	19,688 psi
PERPENDICULAR TO RIFT, WET	13,472 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,081 psi
PARALLEL TO RIFT, WET	1,855 psi
PERPENDICULAR TO RIFT, DRY	2,189 psi
PERPENDICULAR TO RIFT, WET	1,825 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,300 psi
PARALLEL TO RIFT, WET	2,110 psi
PERPENDICULAR TO RIFT, DRY	1,249 psi
PERPENDICULAR TO RIFT, WET	1,683 psi



(573) 302-8855

